# ANEMOI®

## AIRMAX

- > Low energy consumption
- > Maximize HVAC systems efficiency
- > Very attractive ROI
- > Lower installation costs
- > Simplified infrastructure equipment
- > Healthier internal condition

## Flexible Solutions for Destratification and Summer Comfort

| Model | Diameter | Maximum speed | Power | Maximum consumption | Maximum current | Air flow* | Recommended coverage** | Maximum coverage** | Operation voltage | Protection | Noise level | Weight |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| AIRMAX 300 | 3m | 135 rpm | 1 kW | 0.97 kW/h | 2,6 A | 134,130 $m^3/h$ | 447 $m^2$ | 626 $m^2$ | 400 VAC | IP65 | 56 dBA | 88 kg |
| AIRMAX 400 | 4m | 100 rpm | 1 kW | 1.04 kW/h | 2.5 A | 202,248 $m^3/h$ | 674 $m^2$ | 943,82 $m^2$ | 400 VAC | IP65 | 54 dBA | 102 kg |
| AIRMAX 500 | 5m | 68 rpm | 1 kW | 0.9 kW/h | 2.3 A | 228,800 $m^3/h$ | 763 $m^2$ | 1,068 $m^2$ | 400 VAC | IP65 | 50 dBA | 108 kg |
| AIRMAX 600 | 6m | 55 rpm | 1 kW | 0.9 kW/h | 2.2 A | 324,901 $m^3/h$ | 1,083 $m^2$ | 1,156 $m^2$ | 400 VAC | IP65 | 50 dBA | 128 kg |
| AIRMAX 660 | 6,6m | 46 rpm | 1 kW | 0.8 kW/h | 2.2 A | 362,337 $m^3/h$ | 1,208 $m^2$ | 1,691 $m^2$ | 400 VAC | IP65 | 49 dBA | 133 kg |

* AMCA certificate 230-99 ** Air speed > 0. 5 m/s *** Air speed > 0. 2 m/s



info@anemoifans.com | anemoifans.com